

SP-RE REAR EXTENDING STICK / PIPE TRAILER SPECS



EXCLUSIVE STANDARD ADDED VALUE:

- Industry Leading Safety, Ease of Use, Low Maintenance and Durability
- No-Bind EZ Slide Stanchions
- Low Center of Gravity
- UHMW Composite Bunk Pads w/ Countersunk Fasteners
- Front Bulkhead to Easily Load and Place Material
- Heavy Duty Winch Straps
- Great Price

CAPACITIES

SP-RE14: 16,100 lbs. GVWR @ 15% Tongue WeightSP-RE20: 22,100 lbs. GVWR @ 15% Tongue Weight

AXLES

SP-RE14: Tandem 7K lbs. TorsionSP-RE20: Tandem 10K lbs. Sprung

WHEELS

• SP-RE14: (4) 16 x 6K / 8 on 6.5 BC w/ Zeroset

• SP-RE20: (4) 17.50 x 6.75 HC / 8 on 6.5 BC w/ 0.19 Inset

TIRES

SP-RE14: (4) ST-235/85R16 LR-G TiresSP-RE20: (4) ST-215/75R17 LR-H Tires

BRAKES

SP-RE14: 12.00" x 2.00" Electric w/ Safety Breakaway Kit
SP-RE20: 12.25" x 3.38" Electric w/ Safety Breakaway Kit

PAYLOAD: ALL FINAL PAYLOADS BASED ON CHOSEN MODEL AND OPTIONS

OVERALL LENGTH

• Bed Length: 33' (Retracted) and 40' (Extended)

• Overall Length: 45.3'

OVERALL WIDTH: 96" & 102" Available

OVERALL WEIGHT: Actual Trailer Weight will Vary with Options & Finishes Chosen.

POLE SEAT HEIGHT: 34"

STANDARD FEATURES

• No-Bind EZ Slide Stanchions

• Oil Bath Hubs (Greaseable Option All)

Electric Brakes

• Wheel Chock Holders

Heavy Duty Winch Straps

Front Bulkhead to Easily Load and Place Material

Low Center of Gravity

POLE SECUREMENT

- Pole Rests: 5" H Beam w/ UHMW Composite Pads
- Winch Binders, Ratcheting Breaker Bar and Bar Pocket

STANDARD TRAILER BODY

- Heavy Duty 12" Channel Frame
- Heavy Duty 6" Channel Crossmembers
- 7-Position Adjustable Hitch
- 3/8" X 36" GR70 Yellow Zinc Safety Chains with Hooks
- 12,000 lbs. Static Front Jack w/ Spring Return

WIRING

- DOT / ICC Approved LED Lights and Conspicuity Reflective Tape
- Internal Cat Track Protects Wiring (and air brakes if applicable)
- Removable Rear Access Door for Cat Track and Wiring
- Sealed Beam, Rubber Mounted Stop, Turn, Tail and Marker Lights
- Plug-and-Play Sealco Wiring Harness
- Breakaway Kit with Absorbed Glass Mat (AGM) Battery

PAINT

- I.M.P.A.C.T Intense Metal pH Acid Cleaning Technology
- Hydrofluoric, Sulfuric, Phosphoric ACID Blend Cleaning Preparation (Re-used sandblasting material can impregnate metals with oil)
- Seams Caulked
- Rust Preventative 2-Part Epoxy Primer
- · Standard Colors: Red, Black, White and CAT Yellow

OPTIONS

- 10-Year Galvanized Structural Warranty (2-Year Painted)
- 10K-HD / 15K / 20K Axles Available w/ Air Brakes
- Anti-Lock Brakes (ABS)
- 3" Lunette Eye
- Wiring Connections Soldered and Sealed w/Heat Shrink Tubing
- Wheel Chocks: Rubber or All Weather Galvanized Grip Strut
- Spare Tire and Mount
- Solar Charged Breakaway Kit