




## PLT-SL POWERLOCK™ REEL TRAILER SPECS



### EXCLUSIVE STANDARD ADDED VALUE:

- POWERLOCK™ Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance and Durability.
  - Safety and Peace of Mind
  - No Pins, Cotters, or Lanyards that Secure the Reel Arbor (which is the most critical safety point).
  - Faster Reel Loading, Unloading, and Deployment Reduces Labor Costs and Fatigue on Workers.

***BUILT FOR SAFETY. BUILT FOR SPEED. BUILT TO LAST.***

## CAPACITIES

- PLT-SL10: 16,100 lbs. GVWR @ 15% Tongue Weight

## AXLES

- PLT-SL10: Tandem 7K lbs. Torsion

## WHEELS

- PLT-SL10: (4) 16 x 6K / 8 on 6.5 BC w/ Zeroset

## TIRES

- PLT-SL10: (4) ST-235/85R16 LR-G Tires

## BRAKES

- PLT-SL10: 12.25" x 2.00" Electric w/ Safety Breakaway Kit

## PAYLOAD: ALL FINAL PAYLOADS BASED ON CHOSEN MODEL AND OPTIONS

### REEL WEIGHT (PAYLOAD)

- PLT-SL10: 10,000 lbs. Approx.

**REEL DIAMETER:** 84" Maximum (custom sizes possible)

**REEL WIDTH:** 60" Maximum (102" Wide Trailer)

**REEL SHAFT DIAMETER:** 2.88" OD, 1.88" ID Reel Drive Bar w/ Centering Collars

**OVERALL LENGTH:** 166.25" Overall Length

**OVERALL WIDTH:** 96" or 102" Overall Width

**OVERALL WEIGHT:** Actual Trailer Weight will Vary with Options & Finishes Chosen.

## STANDARD FEATURES

• **PINLESS POWERLOCK™ LIFETIME WARRANTY**

**VIRTUALLY ZERO MAINTENANCE** Yellow Zinc Electroplated

• **INDUSTRY LEADING 20" OVERSIZED TURRET BEARING w/ HYDRAULIC WORM GEAR**

• **250K Axial, 90K ft/lbs Moment Load**

• **OPEN TOP, "NON ENCAPSULATED" NYLATRON BEARING SADDLE**  
(low-coefficient of friction). OPEN TOP = LESS FRICTION/LOW

*—All specifications / designs are subject to change without notice - All GVWR and reel capacities are de-rateable to your needs.*

## **STANDARD FEATURES (cont.)**

MAINTENANCE and EASIER PAY-OUT. (Haven't Replaced a Saddle in 13 Years)

- POWERLOCK™ Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance and Durability.
- Oil Bath Hubs (Greaseable Option All)
- Electric Brakes
- Wheel Chock Holders
- Removable Turrets to Turn Trailer into Flatbed, if Needed.

## **STANDARD TRAILER BODY**

- Heavy Duty 6" X 4" X ¼" Frame
- 6-Position Adjustable Hitch
- ¾" X 36" GR70 Yellow Zinc Safety Chains with Hooks
- 12,000 lbs. Static Front Jack w/ Spring Return
- Ground Lug: Copper Alloy Bolted to Frame
- Fenders: ½" Plate
- Quick Deploy Outriggers (no loose pins)
- Spring Plunger Accessory Engagement

## **WIRING**

- DOT / ICC Approved LED Lights and Conspicuity Reflective Tape
- FMVSS / CMVSS Standard 108 LED Lighting
- Sealed Beam, Rubber Mounted Stop, Turn, Tail and Marker Lights
- Plug-and-Play Sealco Wiring Harness
- Breakaway Kit with Absorbed Glass Mat (AGM) Battery

## **PAINT**

- I.M.P.A.C.T Intense Metal pH Acid Cleaning Technology
- Hydrofluoric, Sulfuric, Phosphoric ACID Blend Cleaning Preparation (Re-used sandblasting material can impregnate metals with oil)
- Seams Caulked
- Rust Preventative 2-Part Epoxy Primer
- Standard Colors: Red, Black, White and CAT Yellow


## **OPTIONS**

- 10-Year Galvanized Structural Warranty (2-Year Painted)
- 13 HP Honda Engine Hydraulic Power Unit
- Engine Cover

## OPTIONS (cont.)

- 3,300 ft/lbs Torque Hydraulic Take-up Retriever. (Motor Spooled w/ Reel Brake ILO Cross-Over Relief Valve for Smooth Instant Reel Stoppage)
- Hydraulic Hose Rotary Swivel Union (*manages & eliminates loose hydraulic hoses*)
- 2-7/16" Universal Adapter for Capstan and Power Reel Attachments
- 7 Inch General Purpose Capstan
- Collapsible Power Reel
- Auxiliary Hydraulic Quick-Connect Ports
- Rewind Leveler
- 16" Bronze Alloy Ventilated Reel Brake
- 16" Hitch Extension
- Aluminum or Steel Toolbox
- Anti-Lock Brakes (ABS)
- 3" Lunette Eye
- Wheel Chocks: Rubber or All Weather Galvanized Grip Strut
- Spare Tire and Mount
- Wiring Connections Soldered and Sealed w/ Heat Shrink Tubing
- Solar Charged Breakaway Kit
- 12" Caster Wheel for Tongue Jack
- Strobe Warning Lights
- All Stainless Steel Fasteners (1/2" and under)
- Hydraulic Front Jack

8 7 6 5 4 3 2 1



UNLESS OTHERWISE SPECIFIED:		DIMENSIONS ARE IN INCHES		TOLERANCE LIMITS	
PROPRIETARY AND CONFIDENTIAL		THE INFORMATION CONTAINED IN THIS		DRAWING IS THE SOLE PROPERTY OF	
REELSTRONG, INC. ANY REPRODUCTION		WITHOUT WRITTEN PERMISSION OF REELSTRONG, INC.		IS PROHIBITED.	
DECIMAL .X = ±0.060		FRACTION 1/16" = ±0.015		DECIMAL .XXX = ±0.005	
MATERIAL:		FINISH:		APPROX WEIGHT:	
DRAWING NO.		DATE		PRODUCTION NO.	
DO NOT SCALE DRAWING		Sheet 1 of 1		SL77K-0000	
REV		1			

PLT-SL10

**REELSTRONG**  
UTILITY FLEET  
PULLERS REEL POLE PULLING TRAILERS AND SERVICE  
V. 484-889-6608 F. 888-303-3932 [info@reelstrong.com](mailto:info@reelstrong.com)