




PLC POWERLOCK™ REEL / CARGO TRAILER SPECS



EXCLUSIVE STANDARD ADDED VALUE:

- POWERLOCK™ Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance and Durability.
 - SAFETY and Peace of Mind
 - No Pins, Cotters, or Lanyards that Secure the Reel Arbor (which is the most critical safety point).
 - Faster Reel Loading, Unloading, and Deployment Reduces Labor Costs and Fatigue on Workers.

BUILT FOR SAFETY. BUILT FOR SPEED. BUILT TO LAST.

CAPACITIES

- PLC10: 16,000 lbs. GVWR @ 15% Tongue Weight
- PLC16: 22,000 lbs. GVWR @ 15% Tongue Weight

AXLES

- PLC10: Tandem 7K lbs. Torsion
- PLC16: Tandem 10K lbs. Sprung

WHEELS (per axle)

- PLC10: (4) 16 x 6K / 8 on 6.5 BC w/ Zeroset
- PLC16: (4) 17.5 x 6.75 HC / 8 on 6.5 BC w/ 0.19 Outset

TIRES (per axle)

- PLC10: (4) ST-235/85R16 LR-E Tires
- PLC16: (4) LT-215/75R17.5 LR-H Tires

BRAKES (per axle)

- PLC10: 12.00" x 2.00" Electric w/ Safety Breakaway Kit
- PLC16: 12.25" x 3.38" Electric w/ Safety Breakaway Kit

PAYLOAD: ALL FINAL PAYLOADS BASED ON CHOSEN MODEL AND OPTIONS

REEL / CARGO WEIGHT (PAYLOAD):

- PLC10: 10,000 lbs. Approx.
- PLC16: 16,000 lbs. Approx.

REEL DIAMETER: 72" Maximum

REEL WIDTH: 54" Maximum

REEL SHAFT DIAMETER: 2.50" Tube w/ Centering Collars

OVERALL LENGTH: 215" Approx. w/o Hitch Extension

OVERALL WIDTH: 96" Overall Width

OVERALL WEIGHT: Actual Trailer Weight will Vary with Options & Finishes Chosen.

STANDARD FEATURES

- POWERLOCK™ Technology provides industry leading safety, ease of use, low maintenance and durability.
- Oil Bath Hubs (Greaseable Option All)
- Electric Brakes

—All specifications / designs are subject to change without notice - All GVWR and reel capacities are de-rateable to your needs.

STANDARD TRAILER BODY

- Heavy Duty 5" X 2" X ¼" Frame
- 6-Position Adjustable Hitch
- ¾" X 36" GR70 Yellow Zinc Safety Chains with Hooks
- 12,000 lbs. Static Front Jack w/ Spring Return
- Ground Lug: Copper Alloy Bolted to Frame
- Fenders: ⅛" Tread Plate
- Steps: ⅛" Tread Plate
- (2) Rear 8,000 lbs. Static Stabilizer Jacks
- Integrated Heavy-Duty Front Toolbox
- Wheel Chock Holders
- Built-in Reel Pockets to Accept Removable Reel Stands
- Cargo Area: 64" Wide x 144" Long
- Bed Sides: 24" Tall

WIRING

- DOT / ICC Approved LED Lights and Conspicuity Reflective Tape
- FMVSS / CMVSS Standard 108 LED Lighting
- Sealed Beam, Rubber Mounted Stop, Turn, Tail and Marker Lights
- Plug-and-Play Sealco Wiring Harness
- Breakaway Kit with Absorbed Glass Mat (AGM) Battery

PAINT

- I.M.P.A.C.T Intense Metal pH Acid Cleaning Technology
- Hydrofluoric, Sulfuric, Phosphoric ACID Blend Cleaning Preparation
(Re-used sandblasting material can impregnate metals with oil)
- Seams Caulked
- Rust Preventative 2-Part Epoxy Primer
- Standard Colors: Red, Black, White and CAT Yellow

OPTIONS

- 10-Year Galvanized Structural Warranty (2-Year Painted)
- 13 HP Honda Engine Hydraulic Power Unit
- Engine Cover
- 3,300 or 3,900 ft/lbs Hydraulic Power Winder (Shown with Capstan & Adapter)
(Comes Standard w/ 2-7/16" Universal Adapter for Capstan and Power Reel Attachments)
- 7 Inch General Purpose Capstan
- Collapsible Power Reel
- Auxiliary Hydraulic Quick-Connect Ports
- Rewind Leveler
- 16" Bronze Alloy Ventilated Reel Brake

OPTIONS (cont.)

- 9" Stainless Steel Overspin Brake
- 16" Hitch Extension
- Aluminum or Steel Toolbox
- Anti-Lock Brakes (ABS)
- 3" Lunette Eye
- Wiring Connections Soldered and Sealed w/ Heat Shrink Tubing
- Wheel Chocks: Rubber or All Weather Galvanized Grip Strut
- Spare Tire and Mount
- Solar Charged Breakaway Kit
- Strobe Warning Lights
- All Stainless Steel Fasteners (½" and under)
- Hydraulic Front Jack

