



GR DUAL-LOCK™ GENERAL DUTY SELF-LOADING REEL TRAILER SPECS



EXCLUSIVE STANDARD ADDED VALUE:

- DUAL-LOCK™ Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance, and Durability.
- SAFETY and Peace of Mind
- No Pins, Cotters, or Lanyards that Secure the Reel Arbor (which is the most critical safety point)
- Faster Reel Loading, Unloading, and Deployment Reduce Labor Costs and Fatigue on Workers.

BUILT FOR SAFETY. BUILT FOR SPEED. BUILT TO LAST.

CAPACITIES

- GR6K: 8,050 lbs. GVWR @ 15% Tongue Weight (available special order)
- GR8K: 11,050 lbs. GVWR @ 15% Tongue Weight
- GR10K: 13,800 lbs. GVWR @ 15% Tongue Weight

AXLES

- GR6K: 7K lbs. Axle
- GR8K: 10K lbs. Axle
- GR10K: 12K lbs. Axle

WHEELS

- GR6K: (2) 16 x 6K / 8 on 6.5 BC w/ Zeroset
- GR8K: (2) 17.5 x 6.75 HC / 8 on 6.5 BC w/ 0.19 Inset
- GR10K: (2) 17.5 x 6.75 HC / 8 on 6.5 BC w/ 0.19 Inset

TIRES

- GR6K: (2) 235/85R16 LR-E Tires
- GR8K: (2) 215/75R17.5 LR-H Tires
- GR10K: (2) 235/75R17.5 LR-H Tires

BRAKES

- GR6K: 12.25" x 3.38" Electric w/ Safety Breakaway Kit
- GR8K: 12.25" x 3.38" Electric w/ Safety Breakaway Kit
- GR10K: 12.25" x 5.00" Electric w/ Safety Breakaway Kit

PAYLOAD: ALL FINAL PAYLOADS BASED ON CHOSEN MODEL AND OPTIONS

REEL WEIGHT (PAYLOAD)

- GR6K: 6,000 lbs. Approx.
- GR8K: 8,500 lbs. Approx.
- GR10K: 10,000 lbs. Approx.

REEL DIAMETER: 125" Maximum

REEL OPENING

- GR6K: 66" Approx.
- GR8K: 64" Approx.
- GR10K: 60" Approx.

REEL SHAFT DIAMETER: 2.50" Solid w/ Centering Collars

OVERALL LENGTH:

- GR6K: 141.25" Approx.
- GR8K: 141.75" Approx.
- GR10K: 143" Approx.

OVERALL WIDTH: 102" Overall Width

OVERALL WEIGHT:

- GR6K: 1,950 lbs. Approx.
- GR8K: 2,200 lbs. Approx.
- GR10K: 2,300 lbs. Approx.

Actual Trailer Weight will Vary with Options & Finishes Chosen.

STANDARD FEATURES

- DUAL-LOCK™ Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance, and Durability.
- Auto-locking Swing Out Reel Bar Retainer w/ Secondary Cylinder Lock
- Oil Bath Hubs (Greaseable Option All)
- Electric Brakes

STANDARD TRAILER BODY

- Heavy Duty 6" X 4" X ¼" Frame
- 6-Position Adjustable Hitch
- ¾" X 36" GR70 Yellow Zinc Safety Chains with Hooks
- 8,000 lbs. Static Front Jack

WIRING

- DOT / ICC Approved LED Lights and Conspicuity Reflective Tape
- FMVSS / CMVSS Standard 108 LED Lighting
- Sealed Beam, Rubber Mounted Stop, Turn, Tail and Marker Lights
- 100% Sealed Heat-Shrunked Wiring Connections w/ Full Loom
- Breakaway Kit with Absorbed Glass Mat (AGM) Battery


PAINT

- I.M.P.A.C.T Intense Metal pH Acid Cleaning Technology
- Hydrofluoric, Sulfuric, Phosphoric ACID Blend Cleaning Preparation (Re-used sandblasting material can impregnate metals with oil)
- Seams Caulked
- Rust Preventative 2-Part Epoxy Primer
- Standard Colors: Red, Black, White and CAT Yellow

OPTIONS

- 13 HP HONDA Engine Hydraulic Power Pack Comes STANDARD w/ ENGINE COVER, 15 Gallon Reservoir, Replaceable Oil Filter, Pressure Gauge and Solar Fade Resistant Plastic Control Placard. (Electric Start Optional)
- 10-Year Galvanized Structural Warranty (2-Year Painted)
- 16" Long 6-Bolt Hitch Extension (w/ 52" Safety Chains and Breakaway Cable Extension)
- 3" Lunette Eye
- Rotating Arbor Ground
- Wiring Connections Soldered and Sealed w/ Heat Shrink Tubing
- Plug-and-Play Sealco Wiring Harness
- Wheel Chocks: Rubber or All Weather Galvanized Grip Strut
- Spare Tire and Mount
- Solar Charged Breakaway Kit
- All Stainless Steel Fasteners (½" and under)
- 13 HP Honda Engine Hydraulic Power Unit
- Engine Cover
- 12V Electric over Hydraulic Power Option
- 9" Bronze Overspin Brake
- Truck-Lite Lighting
- Lug Nut Indicators

1 2 3 4 5 6 7 8



UNLESS OTHERWISE SPECIFIED:		TITLE: GR6K	
PROPERTY AND CONFIDENTIAL THE INFORMATION CONTAINED HEREIN IS UNCLASSIFIED DRAWING IS THE SOLE PROPERTY OF Reelstrong Inc. ANY REPRODUCTION OR USE OF THIS DRAWING WITHOUT THE WRITTEN PERMISSION OF Reelstrong, Inc. IS PROHIBITED.	DIMENSIONS ARE IN INCHES TOLERANCE LIMITS: ANGULAR $\pm 1.0^\circ$ DECIMAL $\pm .0010$ FRACTIONAL $\pm .0005$ DECIMAL $\pm .0005$	MATERIAL:	
		FINISH:	
		APPROX. WEIGHT:	
		SHEET 9 OF 11	DATE: 8/4/2017
		DRAWING NOT TO SCALE	




REELSTRONG.
UTILITY FLEET

PHILIPPSBURG, PA 17033
283 S. Oak St., Monaca, PA 17043

V: 484-889-8248 F: 888-380-3932 info@reelstronginc.com

**REELSTRONG**
UTILITY FLEET

PHILIPPS REEL POLE PULLING HEADERS AND SERVICE
10000 W. 100th St., Suite 100, Overland Park, KS 66213
P: 913.241.1234 F: 913.241.1235
Y: 484-895-8248 F: 888-310-3932 info@reelstrongfleet.com



UNLESS OTHERWISE SPECIFIED:

ALL DIMENSIONS ARE IN INCHES
TOLERANCE LIMITS:
ANGULAR ± 1.0°
DECIMAL .XX ± 0.005
DECIMAL .XXX ± 0.010
DECIMAL .XXXX ± 0.005


IF ANY DIMENSION IS NOT SPECIFIED IN THE DRAWING, THE DIMENSION SHALL BE AS SHOWN ON THE DRAWING. ANY REPRODUCTION OF THIS DRAWING WITHOUT THE WRITTEN PERMISSION OF ReelStrong, Inc. IS PROHIBITED.



MATERIAL:	
FINISH:	
APPROX WEIGHT:	
SHEET 10 OF 11	
DATE	8/4/2017
PART NO.	Model GR Universal

TITLE:	GR8K
DATE	8/4/2017
PART NO.	Model GR Universal
1	

8 7 6 5 4 3 2 1



UNLESS OTHERWISE SPECIFIED:		REELSTRONG [®] UTILITY FLEET		TITLE: GR10K	
PROPERTY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF REELSTRONG, INC. ANY REPRODUCTION OR TRANSMISSION OF THIS DRAWING WITHOUT THE WRITTEN PERMISSION OF REELSTRONG, INC. IS PROHIBITED.	DIMENSIONS ARE IN INCHES TOLERANCE LIMITS: ANGULAR ± 1.0° DECIMAL .005 FRACTIONAL 1/16 DECIMAL .XXX ± 0.005	MATERIAL: FINISH: APPX WEIGHT:		DATE: 8/4/2017	
		SHEET 11 OF 11		PART NO. Model GR Universal	
		DRAWING NOT TO SCALE		1	

8 7 6 5 4 3 2 1